

FPD4-0.01-100-1K-N

4-Way, 0.01~100MHz

Features:

- * Small Size
- * Low Insertion Loss

Applications:

- * Amplifiers
- * Mixers
- * Antennas
- * Laboratory Test

Electrical

Frequency:	0.01~100MHz
Insertion Loss ^{*1} :	0.5dB max.
Input VSWR:	1.3 max.
Output VSWR:	1.4 max.
Isolation:	18dB min.
Amplitude Balance:	±0.1dB max.
Phase Balance:	±3° max.
Power @SUM Port:	1000W as divider 1000W as combiner

[1] Excluding theoretical loss 6.0dB.

Mechanical

Size ^{*2} :	270*184*85mm 10.63*7.244*3.346in
Connectors:	N Female
Mounting:	10-Φ4.5mm through-hole


[2] Exclude connectors.

How To Order

FPD4-0.01-100-1K-N

Customization is available upon request.

Outline Drawings



Note: Fan size 40mm * 40mm * 20mm, rated voltage 24V, air volume greater than or equal to 0.2m³/min.

Fan power supply: The red line is the positive pole, the black line is the negative pole, and the wind direction blows inside the product. The model of the power plug is 2.5/2pin.

Unit: mm [in]

Tolerance: ±0.3mm [±0.012in]