

FPD4-400-4000-30-S


4-Way, 0.4~4GHz

Features:

- * Small Size
- * Low Insertion Loss

Applications:

- * Amplifiers
- * Mixers
- * Antennas
- * Laboratory Test



Electrical

Frequency:	0.4~4GHz
Insertion Loss ^{*1} :	1.4dB max.
Input VSWR:	1.35 max.
Output VSWR:	1.2 max.
Isolation:	18dB min.
Amplitude Balance:	±0.3dB
Phase Balance:	±4°
Impedance:	50Ω
Power @SUM Port:	30W max. as divider 2W max. as combiner

[1] Excluding theoretical loss 6.0dB.

Mechanical


Size ^{*2} :	88*70*12mm 3.465*2.756*0.472in
Connectors:	SMA Female
Mounting:	4-Φ3.2mm through-hole

[2] Exclude connectors.

Environmental

Operation Temperature:	-35~+75°C
------------------------	-----------

Outline Drawings



Unit: mm [in]



Tolerance: ±0.5mm [±0.02in]

How To Order

FPD4-400-4000-30-S


Customization is available upon request.

Typical Performance Curves




4-Way Power Divider/Combiner


Insertion Loss vs. Frequency



Isolation vs. Frequency



Amplitude Balance vs. Frequency



Phase Balance vs. Frequency

