

FPD4-4000-12000-30-S

4-Way, 4~12GHz

Features:

- * Small Size
- * Low Insertion Loss

Applications:

- * Amplifiers
- * Mixers
- * Antennas
- * Laboratory Test

Electrical

Frequency:	4~12GHz
Insertion Loss ^{*1} :	1.2dB max.
Input VSWR:	1.4 max.
Output VSWR:	1.3 max.
Isolation:	18dB min.
Amplitude Balance:	±0.2dB
Phase Balance:	±5°
Impedance:	50Ω
Power @SUM Port:	30W max. as divider 2W max. as combiner

[1] Excluding theoretical loss 6.0dB.

Mechanical


Size ^{*2} :	60*40*10mm 2.362*1.575*0.394in
Connectors:	SMA Female
Mounting:	4-Φ2.7mm through-hole

[2] Exclude connectors.

Environmental

Operation Temperature:	-45~+85°C
------------------------	-----------

Outline Drawings



Unit: mm [in]



Tolerance: ±0.5mm [±0.02in]

How To Order

FPD4-4000-12000-30-S


Customization is available upon request.

Typical Performance Curves




4-Way Power Divider/Combiner


Insertion Loss vs. Frequency



Isolation vs. Frequency



Amplitude Balance vs. Frequency



Phase Balance vs. Frequency

