

FWCK-430

WR-430, 1.72~2.61GHz

Features:


- * Broad Band
- * Low VSWR

Applications:

- * Calibration
- * Laboratory Test

Components

Part Number	Frequency (GHz)	VSWR (Max.)	Description	Material	Finish	Coating	Quantity (pcs)	Outline Drawings
FWCA-430-SF-R-2-1	1.72~2.61	1.2	Waveguide to coax adapter, WR-430 (BJ22) to SMA(f), right angle, FDP22	Aluminium	Conductive oxidation	Black paint	2	Outline A
FWT430-A-2	1.72~2.61	1.03	Low power waveguide termination, WR-430 (BJ22), FDP22	Aluminium	Conductive oxidation	Sea gray	1	Outline B
FWS430-A-2	1.72~2.61	-	Waveguide short, WR-430 (BJ22), Xmm, FDP22	Aluminium	-	-	1	Outline D
FWSS430-X-A-2	1.72~2.61	-	1/4λ Waveguide straight section, WR-430 (BJ22), Xmm, FDP22	Aluminium	-	-	1	Outline C
Storage Box	Aluminum Alloy						1	-
Screw							1 set	-

Outline Drawings


Unit: mm [in]

Tolerance: ±0.5mm [±0.02in]

Environmental

Operating Temperature: -40~+85°C

Non-operating Temperature: -50~+80°C

How To Order**FWCK-430** All the 5 components in one box.