

FASN-B6

SMA to N

Features:

- * Low VSWR

Applications:

- * Wireless
- * Transmitter
- * Laboratory Test
- * Radar



Electrical

Frequency:	DC~6GHz
VSWR:	1.15 max. 1.2 max. (Outline I) 1.3 max. (Outline J)
Dielectric Withstanding Voltage:	1000V RMS, 50Hz, at sea level min. (Outline I, J)
Impedance of Dielectric:	5000MΩ min. (Outline I, J)
Impedance of Contact (Center):	1mΩ max. (Outline I, J) 3mΩ max. (Outline I, J)
Impedance of Contact (Outer):	0.2mΩ max. (Outline I, J) 2mΩ max. (Outline I, J)
Impedance:	50Ω


Environmental

Temperature:	-55~+165°C -45~+125°C (Outline I, J)
--------------	---


Mechanical

RF Connectors:	SMA N
Mating Life Cycle:	500 cycles
Outer Conductor:	Ternary alloy plated brass Nickel plated brass (Outline I, J)
Dielectric:	PTFE
Inner Conductor:	Gold Plated Beryllium Copper Gold plated brass (Outline I, J)


Outline Drawings



Coaxial Adapters



Outline I



Outline J

Unit: mm [in]

Tolerance: $\pm 0.2\text{mm}$ [$\pm 0.008\text{in}$]

How To Order

FASN-MM-B6 - SMA (m) to N (m), Outline A

FASN-MF-B6 - SMA (m) to N (f), Outline B

FASN-FM-B6 - SMA (f) to N (m), Outline C

FASN-FF-B6 - SMA (f) to N (f), Outline D

FASNL-FF-B6 - SMA (f) to N (f) flange mount, Outline E

FASNH-FF-B6 - SMA (f) to N (f) bulk head, Outline F

FASNH-FF-B6-1 - SMA (f) to N (f) bulk head, Outline G

FASNH-FF-B6-2 - SMA (f) to N (f) bulk head, Outline H

FASNH-MF-B6 - SMA (m) to N (f) bulk head, Outline I

FASNRL-FF-B6 - SMA (f) to N (f) right angle, flange mount, Outline J

Customization is available upon request.